



FURTHER HIGH-GRADE GOLD RESULTS AT 100% OWNED MINYARI DEPOSIT

Highlights

- Further 11 Minyari deposit drill hole assays return significant high-grade gold and copper (± silver and cobalt) intersections, including:
 - 134.0m at 1.70 g/t gold and 0.30% copper from 212.0m down hole in 21MYC0233, including:
 - 1.0m at 5.93 g/t gold, 4.42% copper, 10.75 g/t silver and 0.10% cobalt from 217.0m
 - o **33.0m at 4.49 g/t gold**, 0.71% copper, 1.79 g/t silver and **0.13% cobalt** from 241.0m, also including:
 - 6.0m at 8.40 g/t gold, 2.70% copper, 6.01 g/t silver and 0.18% cobalt from 241.0m;
 - 1.0m at 22.00 g/t gold, 0.44% copper and 2.92 g/t silver from 252.0m;
 - 4.0m at 9.27 g/t gold, 0.90% copper, 2.57 g/t silver and 0.33% cobalt from 259.0m;
 - o **8.0m at 2.97 g/t gold** and 0.47% copper from 327.0m, also including:
 - 2.0m at 7.98 g/t gold, 1.30% copper and 1.80 g/t silver from 327.0m
 - **30.0m at 2.95 g/t gold** and 0.14% copper from 149.0m down hole in 21MYC0235 (further results pending), including:
 - o 8.0m at 9.95 g/t gold, 0.38% copper and 0.13% cobalt from 149.0m, also including:
 - 3.0m at 22.63 g/t gold, 0.58% copper, 1.41 g/t silver and 0.20% cobalt from 154.0m
 - **77.0m at 1.26 g/t gold**, 0.41% copper and 1.10 g/t silver from 85.0m down hole in 21MYC0221, including:
 - o 1.0m at 7.67 g/t gold, 2.82% copper, 8.17 g/t silver and 0.11% cobalt from 85.0m
 - 21.0m at 2.64 g/t gold, 0.91% copper and 2.22 g/t silver from 115.0m, also including:
 - 2.0m at 12.35 g/t gold, 2.38% copper, 5.21 g/t silver and 0.11% cobalt from 134.0m
 - **44.0m at 1.49 g/t gold** and 0.15% copper from 395.0m down hole in 21MYCD0220 (further results pending), including:
 - o **3.0m at 6.69 g/t gold,** 0.26% copper and 1.99 g/t silver from 411.0m; and
 - 3.0m at 6.82 g/t gold, 0.87% copper and 1.41 g/t silver from 434.0m
 - **32.0m at 1.34 g/t gold** and 0.19% copper from 55.0m down hole in 21MYC0227 (further results pending), including:
 - 11.0m at 2.87 g/t gold and 0.33 copper from 76.0m, also including:
 - 1.0m at 14.65 g/t gold, 1.48% copper, 3.14 g/t silver and 0.30% cobalt from 84.0m
- Results continue to extend the potential size of the Minyari resource and enhance the project development opportunity
- 37,620m of Resource definition, Resource extensional and brownfield plus greenfield discovery drilling at Minyari Dome completed – three drill rigs currently on site (awaiting assays for 28,370m)
- Drill programme further expanded to 45,000m

Antipa Minerals Limited (ASX: **AZY**) (**Antipa** or the **Company**) is pleased to announce further assay results for the 2021 drill programme on its 100% owned, 144km² Minyari Dome Project in Western Australia's Paterson Province (Figure 13). The Project is located within 35km of Newcrest Mining's (**Newcrest**) Telfer gold-copper-silver mine and mineral processing facility and 54km along strike from Greatland Gold-Newcrest's Havieron gold-copper development project (Figure 14).

Antipa's Managing Director, Roger Mason, said:

"Minyari drill hole results continue to demonstrate the capacity of this intrusion related breccia system to generate strong gold-copper intersections over wide intervals and highlight significant zones of mineralisation outside the resource to the east and west which will support a revised resource estimate and project development studies for a potential standalone open pit and underground mining operation.

At Minyari, high-grade gold \pm copper, silver and cobalt mineralisation has now been intersected along 500m of strike, down to 600m below the surface and across a horizontal width of up to 275m, and mineralisation remains open in several directions.

Given the success of the program to date, the 2021 drill programme has been further expanded to 45,000 metres and is now expected to be completed in November."

Summary of Drill Programme Objectives

The 2021 drill programme, which commenced in early May, is designed to:

- 1. Test for extensions of both the Minyari and WACA resources, which combined host a JORC 2012 Mineral Resource Estimate of 723koz gold at 2.0 g/t and 26kt copper at 0.24%¹ (Figure 12):
- 2. Explore for new zones of mineralisation proximal to the existing resources such as the new Minyari East discovery;
- 3. Elevate the existing Mineral Resource JORC classification via 25m infill drill sections (i.e. designed to upgrade the existing Inferred sections of the Resource to Indicated and the Indicated sections to Measured Mineral Resource); and
- 4. Provide the basis for project development studies.

Summary of Drilling Results Received to Date

Assay results have now been received for 27 reverse circulation (**RC**) drill holes, three diamond-tail and one diamond core (**DD**) drill hole in total (7,570m), which demonstrate favourable compatibility with the current Mineral Resource domains and have discovered significant additional high-grade gold-copper mineralisation immediately east and west of the existing Minyari resource, including at Minyari East. The drill results, which are both resource definition and extensional in nature, continue to extend the potential size of the Minyari Resource and enhance the project development opportunity.

For detailed information relating to the latest drill holes with assay results refer to Tables 1 and 2 and Figures 1 to 11.

¹ Mineral Resource information refer to Competent Person's statement and table to the rear of this Release

Assays received to date represent just 25% of the Minyari Dome Resource infill, Resource extensional and discovery 2021 drilling programme completed to date and, significantly, have:

- proven that significant zones of very high-grade gold-copper-silver-cobalt mineralisation exist outside the current Minyari deposit Mineral Resource estimate boundary (Figure 1);
- discovered new high-grade gold-copper mineralisation at Minyari East which extended the overall width of the Minyari mineralisation envelope out to approximately 290m (Figures 1 to 10);
- further confirmed that high-grade mineralisation is commonly associated with sulphide matrixed breccia zones similar to the Havieron gold-copper style of mineralisation; and
- confirmed Minyari mineralisation remains open down plunge, along strike and variously open across strike to the east and west.

Due to the correlation between high-grade mineralisation and (conductive) sulphide rich breccias a downhole electromagnetic (**DHEM**) survey will be completed during the second half of November for a selection of diamond core drill holes. DHEM has the ability to identify high-grade targets within 100 to 200m of surveyed drill holes, including four deep holes (average hole depth 940m), which will optimise follow-up drill testing.

Minyari Dome High Priority Targets and Minyari Dome CY21 Exploration Programme

Further information regarding programme modifications will be provided following completion of the Company's ongoing review.

Release authorised by Stephen Power Chairman

For further information, please visit <u>www.antipaminerals.com.au</u> or contact:

Roger Mason	Stephen Power	Angela East
Managing Director	Chairman	Associate Director
Antipa Minerals Ltd	Antipa Minerals Ltd	Media & Capital Partners
+61 (0)8 9481 1103	+61 (0)8 9481 1103	+61 (0)428 432 025




Figure 1: Minyari deposit cross-section view showing only the 2020 (3 holes) and 2021 drill hole gold intercepts which post-date the 2017 Mineral Resource (brown wireframes). Note the abundant mineralisation discovered to the east, west and between the 2017 resource, with the deposit still remaining open in several directions.

NB: 100m Elevation grid (MGA mRL), looking toward Local 160° (or 192° MGA Zone 51).




Figure 2: Minyari gold-copper-silver-cobalt deposit 100,750mN cross-section showing high-grade gold drill intercepts, with the deposit open down dip and along strike/plunge.




Figure 3: Minyari gold-copper-silver-cobalt deposit 100,725mN cross-section showing high-grade gold drill intercepts, with the deposit open down dip and along strike/plunge.




Figure 4: Minyari gold-copper-silver-cobalt deposit 100,700mN cross-section showing high-grade gold drill intercepts, with the deposit open down dip and along strike/plunge.




Figure 5: Minyari gold-copper-silver-cobalt deposit 100,625mN cross-section showing high-grade gold drill intercepts, with the deposit open down dip and along strike/plunge.




Figure 6: Minyari gold-copper-silver-cobalt deposit 100,775mN cross-section showing high-grade gold drill intercepts, with the deposit open down dip and along strike/plunge.




Figure 7: Minyari gold-copper-silver-cobalt deposit 100,550mN cross-section showing high-grade gold drill intercepts, with the deposit open down dip and along strike/plunge.




Figure 8: Minyari gold-copper-silver-cobalt deposit 100,600mN cross-section showing high-grade gold drill intercepts, with the deposit open down dip and along strike/plunge.




Figure 9: Minyari gold-copper-silver-cobalt deposit 100,525mN cross-section showing high-grade gold drill intercepts, with the deposit open down dip and along strike/plunge.

NB: 200m Local Grid co-ordinates, looking toward Local 360° (or 328° MGA Zone 51).




Figure 10: Minyari gold-copper-silver-cobalt deposit 100,500mN cross-section showing high-grade gold drill intercepts, with the deposit open down dip and along strike/plunge.




Figure 11: Minyari deposit Plan view showing distribution of gold-copper mineralisation, and northern and southern target areas. NB: Over Airborne magnetic image (50m flight-line spacing at an altitude of 30m; grey-scale TMI-RP) and 200m Local Grid co-ordinates.




Figure 12: Map of the southern region of the Minyari Dome Project showing Minyari and WACA resource locations, Judes prosect and GAIP07-09 target locations, and drill hole maximum downhole gold and copper. NB: Over Airborne magnetic image (50m flight-line spacing at an altitude of 30m; grey-scale TMI-RP) and Regional GDA2020 / MGA Zone 51 co-ordinates, 1km grid.




Figure 13: Plan showing location of Antipa 100% owned tenements, Rio Tinto-Antipa Citadel Joint Venture Project, including the Calibre and Magnum deposits. Also shows Antipa-Newcrest Wilki Farmin, Antipa-IGO Paterson Farm-in, Newcrest Mining Ltd's Telfer Mine and O'Callaghans deposit, Rio Tinto's Winu deposit, Greatland Gold plc's/Newcrest's Havieron deposit and Cyprium's Nifty Mine.

NB: Rio and IGO tenement areas include related third-party Farm-in's/Joint Ventures.

NB: Regional GDA2020 / MGA Zone 51 co-ordinates, 50km grid.




Figure 14: Project Location map showing Antipa's Minyari Dome (100%) Project and proximity to Newcrest Mining Ltd's Telfer Gold-Copper-Silver mine and processing facility.

NB: Regional GDA2020 / MGA Zone 51 co-ordinates, 10km grid.

Table 1: Latest Significant intersections from Minyari deposit 2021 drill programme

Hole ID	Area	From (m)	To (m)	Interval (m)	Gold (g/t)	Copper (%)	Silver (g/t)	Cobalt (ppm)
21MYC0221	Minyari	22.0	23.0	1.0	1.32	0.81	1.70	36
21MYC0221	Minyari	37.0	38.0	1.0	0.16	0.13	0.20	239
21MYC0221	Minyari	40.0	42.0	2.0	0.58	0.03	0.11	168
21MYC0221	Minyari	70.0	71.0	1.0	0.18	0.16	0.41	115
21MYC0221	Minyari	83.0	84.0	1.0	0.36	0.14	0.51	361
21MYC0221	Minyari	85.0	162.0	77.0	1.26	0.41	1.10	477
	Including	85.0	87.0	2.0	5.23	1.83	9.39	790
	Also Incl.	85.0	86.0	1.0	7.67	2.82	8.17	1,080
	Including	115.0	136.0	21.0	2.64	0.91	2.22	586
	Also Incl. Also Incl.	115.0 116.0	116.0 118.0	1.0 2.0	1.78 4.51	5.06 0.48	9.99 1.59	1,800 1,328
	Also Incl.	121.0	122.0	1.0	4.51	3.25	7.72	876
	Also Incl.	122.0	124.0	2.0	2.37	1.24	4.41	375
	Also Incl.	133.0	134.0	1.0	2.66	1.23	2.43	456
	Also Incl.	134.0	136.0	2.0	12.35	2.38	5.21	1,007
	Including	143.0	144.0	1.0	3.18	0.33	1.17	335
	Including	144.0	145.0	1.0	0.79	1.53	3.07	468
	Including	158.0	161.0	3.0	3.57	0.57	1.05	1,296
21MYC0221	Minyari	166.0	167.0	1.0	0.60	0.08	0.06	324
21MYC0221	Minyari	188.0	193.0	5.0	0.57	0.04	0.04	82
2200222	Including	192.0	193.0	1.0	1.42	0.04	0.03	153
21MYC0221	Minyari	206.0	207.0	1.0	0.61	0.00	0.00	27
21MYC0221	Minyari	232.0	248.0	16.0	1.18	0.11	0.20	95
	Including	232.0	233.0	1.0	3.12	0.06	0.15	94
	Including	242.0	247.0	5.0	2.53	0.18	0.34	110
	Also Incl.	242.0	243.0	1.0	5.26	0.51	1.04	129
	Also Incl.	246.0	247.0	1.0	4.06	0.20	0.30	218
21MYC0221	Minyari	248.0	249.0	1.0	0.23	0.11	0.15	136
21MYC0221	Minyari	252.0	253.0	1.0	0.52	0.03	0.10	43
21MYC0221	Minyari	281.0	300.0	19.0	1.57	0.12	0.22	29
2200222	Including	284.0	286.0	2.0	10.08	0.45	1.22	95
21MYC0221	Minyari	302.0	303.0	1.0	0.46	0.09	0.11	20
21MYC0221	Minyari	329.0	330.0	1.0	0.03	0.10	0.15	117
21MYC0221	Minyari	344.0	345.0	1.0	0.20	0.15	0.23	37
21MYC0221	Minyari	351.0	415.0	64.0	1.42	0.10	0.48	38
	Including	352.0	354.0	2.0	20.75	1.08	2.91	186
	Including	379.0	380.0	1.0	3.06	0.05	0.15	50
	Including	386.0	387.0	1.0	3.12	1.02	1.49	222
	Including	399.0	401.0	2.0	14.75	0.09	8.27	162
	Also Incl.	399.0	400.0	1.0	25.00	0.18	15.95	294
21MYC0224	Minyari	73.0	75.0	2.0	0.14	0.14	0.38	198
21MYC0224	Minyari	88.0	89.0	1.0	0.42	0.02	0.04	373
21MYC0224	Minyari	139.0	223.0	84.0	0.61	0.27	0.71	186
	Including	139.0	140.0	1.0	2.05	0.03	0.05	105
21MYC0224	Minyari	153.0	154.0	1.0	0.93	1.81	3.72	289
21MYC0224	Minyari	165.0	168.0	3.0	2.68	1.10	2.88	840
21MYC0224	Minyari	180.0	205.0	25.0	1.06	0.47	1.30	242
	Also Incl.	180.0	181.0	1.0	2.94	2.17	5.42	1,655
21MYC0224	Minyari	189.0	193.0	4.0	1.69	1.25	3.70	471
21MYC0224	Minyari	198.0	202.0	4.0	2.63	0.52	1.33	248
	including	218.0	222.0	4.0	1.59	0.53	1.20	269
2414/00024	also incl.	219.0	220.0	1.0	2.06	1.19	2.58	202
21MYC0224	Minyari	266.0	267.0	1.0	0.72	0.02	0.03	74
21MYC0224	Minyari	279.0	282.0	3.0	3.94	0.01	0.12	193
2414/00224	Including	279.0	280.0	1.0	10.55	0.02	0.22	493
21MYC0224	Minyari	295.0	296.0	1.0	0.84	0.07	0.20	38
21MYC0224 21MYC0224	Minyari	335.0	336.0	1.0	0.42	0.29	0.73	33
Z11VI I CUZZ4	Minyari Including	353.0 358.0	359.0 359.0	6.0 1.0	0.87 4.11	0.05 0.19	0.17 0.94	46 119
21MYC0224	Minyari	358.0	359.0	1.0	0.40	0.19	0.94	119
21MYC0224 21MYC0224	Minyari	374.0	385.0	1.0	0.40	0.04	0.09	40
Z 11V11 CUZZ4	Including	374.0	383.0	11.0	1.33	0.09	0.19	61
21MYC0224	Minyari	389.0	390.0	1.0	0.27	0.17	0.40	32
21MYC0224 21MYC0225	Minyari	1.0	5.0	4.0	1.01	0.10	0.13	17
Z 1 W 1 C U Z Z 3	including	4.0	5.0	1.0	2.35	0.05	0.11	20
21MYC0225	Minyari	14.0	25.0	11.0	0.04	0.10	0.18	91
21.111 00223	•	31.0	32.0	1.0	0.14	0.10	0.08	33
21MYC0225	Minyari	31.0	3711					

Hole ID	Area	From (m)	To (m)	Interval (m)	Gold (g/t)	Copper (%)	Silver (g/t)	Cobalt (ppm)
21MYC0226	Minyari	100.0	126.0	26.0	0.47	0.17	0.58	21
21MYC0226	Minyari	125.0	126.0	1.0	1.41	0.38	1.18	68
21MYC0226	Minyari	129.0	130.0	1.0	0.10	0.12	0.25	6
21MYC0226	Minyari	133.0	134.0	1.0	0.10	0.11	0.24	3
21MYC0226	Minyari	159.0	160.0	1.0	0.83	0.27	0.59	5
21MYC0226	Minyari	166.0	167.0	1.0	0.22	0.18	0.30	g
21MYC0226	Minyari	183.0	184.0	1.0	1.07	0.20	0.50	11
21MYC0226	Minyari	184.0	186.0	2.0	0.27	0.13	0.25	7
21MYC0226	Minyari	197.0	198.0	1.0	0.72	0.02	0.05	
21MYC0227 ¹	Minyari	0.0	4.0	4.0	0.43	0.01	0.12	
21MYC0227 ¹	Minyari	20.0	24.0	4.0	0.29	0.11	0.09	10
21MYC0227	Minyari	24.0	33.0	9.0	1.74	0.32	0.03	18
21MYC0227	•	33.0	34.0	1.0	0.32	0.32	0.27	14
	Minyari							
21MYC0227 ¹	Minyari	51.0	52.0	1.0	0.29	0.20	0.09	23
21MYC0227 ¹	Minyari	55.0	87.0	32.0	1.34	0.19	0.29	37
	Including	76.0	87.0	11.0	2.87	0.33	0.58	63
	Also Incl.	78.0	79.0	1.0	4.04	0.43	0.59	72
	Also Incl.	84.0	85.0	1.0	14.65	1.48	3.14	2,95
21MYC0227 ¹	Minyari	93.0	94.0	1.0	0.23	0.11	0.18	4
21MYC0227 ¹	Minyari	121.0	123.0	2.0	0.46	0.04	0.07	30
21MYC0227 ¹	Minyari	128.0	132.0	4.0	0.75	0.12	0.29	27
	Including	129.0	130.0	1.0	1.20	0.24	0.60	62
21MYC0227 ¹	Minyari	138.0	139.0	1.0	0.24	0.36	0.98	7
21MYC0227	Minyari	139.0	141.0	2.0	1.43	0.30	1.67	16
2 1 W 1 COZZ /								
24 1 41/022271	Including	139.0	140.0	1.0	2.38	1.33	3.08	26
21MYC0227 ¹	Minyari	147.0	148.0	1.0	2.86	0.33	0.49	25
21MYC0227 ¹	Minyari	155.0	158.0	3.0	3.22	0.09	0.31	37
	Including	155.0	156.0	1.0	7.18	0.17	0.55	14
21MYC0228	Minyari	76.0	87.0	11.0	0.51	0.09	0.24	7
	including	85.0	87.0	2.0	1.48	0.24	0.72	16
21MYC0228	Minyari	103.0	104.0	1.0	0.40	0.04	0.10	6
21MYC0228	Minyari	175.0	176.0	1.0	0.02	0.11	0.14	6
21MYC0228	Minyari	254.0	255.0	1.0	0.08	0.11	0.19	3
21MYC0228	Minyari	271.0	272.0	1.0	0.10	0.13	0.19	2
21MYC0233	Minyari	212.0	346.0	134.0	1.70	0.30	0.72	53
21101100233	•	217.0		1.0		4.42	10.75	
	including		218.0		5.93			1,02
	including	241.0	274.0	33.0	4.49	0.71	1.79	1,28
	also incl.	241.0	247.0	6.0	8.40	2.70	6.01	1,80
	also incl.	252.0	253.0	1.0	22.00	0.44	2.92	30
	also incl.	259.0	263.0	4.0	9.27	0.90	2.57	3,32
	also incl.	264.0	265.0	1.0	11.00	0.36	1.21	1,52
	also incl.	267.0	268.0	1.0	8.37	0.66	1.62	1,63
	including	308.0	309.0	1.0	4.51	0.04	0.08	3,13
	including	312.0	313.0	1.0	2.86	0.05	0.09	10
	including	327.0	335.0	8.0	2.97	0.47	0.66	-
	also incl.	327.0	329.0	2.0	7.98	1.30	1.80	13
	including	339.0	340.0	1.0	5.06	0.80	1.28	
21MYC0233	Minyari	368.0	369.0	1.0	0.24	0.80	0.29	į
	•							
21MYC0233	Minyari	422.0	423.0	1.0	0.11	0.11	0.39	:
21MYC0233	Minyari	433.0	434.0	1.0	0.96	0.19	0.46	:
21MYC0235 ¹	Minyari	52.0	53.0	1.0	0.07	0.10	0.08	
21MYC0235 ¹	Minyari	64.0	65.0	1.0	0.44	0.51	0.61	17
21MYC0235 ¹	Minyari	65.0	73.0	8.0	0.10	0.11	0.13	
21MYC0235 ¹	Minyari	140.0	141.0	1.0	0.02	0.11	0.13	1:
21MYC0235 ¹	Minyari	144.0	145.0	1.0	0.30	0.12	0.28	1:
21MYC0235 ¹	Minyari	147.0	148.0	1.0	0.24	0.11	0.24	19
21MYC0235 ¹	Minyari	149.0	179.0	30.0	2.95	0.14	0.29	4:
	including	149.0	157.0	8.0	9.95	0.38	0.86	1,29
	also incl.	154.0	157.0	3.0	22.63	0.58	1.41	1,9
21MYC0236	Minyari	40.0	41.0	1.0	0.46	0.04	0.10	1,5
21MYC0236	Minyari	47.0	48.0	1.0	0.43	0.04	0.10	
	•							
21MYC0236	Minyari	59.0	60.0	1.0	0.67	0.38	0.75	44
21MYC0236	Minyari	68.0	70.0	2.0	0.63	0.11	0.28	10
21MYC0236	Minyari	159.0	160.0	1.0	0.29	0.14	0.46	
21MYC0236	Minyari	168.0	170.0	2.0	0.93	0.18	0.41	3
	Including	168.0	169.0	1.0	1.46	0.22	0.53	3
21MYC0236	Minyari	199.0	200.0	1.0	0.54	0.01	0.04	
21MYC0236	Minyari	207.0	213.0	6.0	1.22	0.01	0.20	30
	including	212.0	213.0	1.0	3.87	0.08	0.48	1,27
211470226						0.19		
21MYC0236	Minyari Including	222.0 222.0	234.0 223.0	12.0 1.0	0.67 1.40	0.04	0.05 0.14	13 27

Hole ID	Area	From (m)	To (m)	Interval (m)	Gold (g/t)	Copper (%)	Silver (g/t)	Cobalt (ppm)
	Including	226.0	228.0	2.0	1.51	0.03	0.15	289
	Including	232.0	233.0	1.0	1.23	0.04	0.04	302
21MYC0236	Minyari	243.0	244.0	1.0	1.33	0.15	0.33	17
21MYC0236	Minyari	275.0	276.0	1.0	7.27	0.38	0.61	535
21MYC0236	Minyari	291.0	293.0	2.0	0.13	0.16	0.15	44
21MYC0236	Minyari	311.0	325.0	14.0	1.91	0.09	0.28	23
	including	311.0	317.0	6.0	2.88	0.17	0.52	36
	Also Incl.	315.0	317.0	2.0	4.99	0.33	1.14	45
21MYC0236	including Minyari	323.0 325.0	325.0	2.0 3.0	4.02 0.53	0.09 0.02	0.24 0.11	24 28
21MYCD0220 ¹	Minyari	30.0	328.0 31.0	1.0	0.00	0.02	0.11	305
21MYCD0220 ¹	Minyari	43.0	48.0	5.0	0.10	0.11	0.16	685
21MYCD0220 ¹	Minyari	48.0	49.0	1.0	0.10	0.10	0.03	748
21MYCD0220 ¹	Minyari	52.0	55.0	3.0	0.00	0.13	0.03	556
21MYCD0220 ¹	Minyari	60.0	61.0	1.0	0.03	0.13	0.02	197
21MYCD0220 ¹	Minyari	63.0	64.0	1.0	0.61	0.10	0.00	186
21MYCD0220 ¹	Minyari	64.0	65.0	1.0	0.01	0.10	0.00	212
21MYCD0220 ¹	Minyari	68.0	69.0	1.0	0.18	0.10	0.02	263
21MYCD0220 ¹	Minyari	74.0	93.0	19.0	0.16	0.58	0.28	470
211111111111111111111111111111111111111	including	80.0	84.0	4.0	0.05	1.80	0.15	907
21MYCD0220 ¹	Minyari	102.0	105.0	3.0	0.05	0.10	0.13	167
21MYCD0220 ¹	Minyari	119.0	120.0	1.0	0.00	0.10	0.18	67
21MYCD0220 ¹	Minyari	123.0	125.0	2.0	0.11	0.10	0.65	19
21MYCD0220 ¹	Minyari	137.0	159.0	22.0	1.03	0.51	1.14	396
211011CD0220	including	137.0	138.0	1.0	2.56	0.39	0.91	436
	including	138.0	139.0	1.0	0.46	1.65	2.96	735
	including	144.0	145.0	1.0	3.30	1.05	3.06	1,110
21MYCD0220 ¹	Minyari	161.0	162.0	1.0	0.12	0.12	0.26	43
21MYCD0220 ¹	Minyari	169.0	181.0	12.0	0.12	0.12	0.20	124
211011CD0220	including	169.0	171.0	2.0	2.81	0.10	0.53	252
21MYCD0220 ¹	Minyari	230.0	231.0	1.0	0.66	0.13	0.04	79
1MYCD0220	Minyari	268.0	269.0	1.0	0.43	0.01	0.05	10
1MYCD0220	Minyari	270.0	287.0	17.0	1.24	0.01	0.36	12
.11011CD0220	including	280.0	282.0	2.0	2.81	0.30	0.75	157
	including	285.0	286.0	1.0	6.55	0.34	1.53	238
1MYCD0220 ¹	Minyari	292.0	293.0	1.0	0.15	0.12	0.23	4:
21MYCD0220 ¹	Minyari	312.0	313.0	1.0	0.13	0.12	0.26	20
21MYCD0220 ¹	Minyari	319.0	320.0	1.0	2.44	0.02	0.05	15
1MYCD0220	Minyari	340.0	342.0	2.0	11.41	0.77	1.99	270
LIWITCDOZZO	including	341.0	342.0	1.0	21.70	1.06	3.29	480
21MYCD0220 ¹	Minyari	353.0	354.0	1.0	0.08	0.10	0.28	29
21MYCD0220 ¹	Minyari	387.0	388.0	1.0	0.66	0.10	0.24	47
21MYCD0220 ¹	Minyari	395.0	439.0	44.0	1.49	0.15	0.26	242
ETIVITODOZZO	Including	397.0	399.0	2.0	4.69	0.23	0.32	8:
	Including	411.0	414.0	3.0	6.69	0.26	0.55	260
	also incl.	411.0	412.0	1.0	13.75	0.43	1.00	56
	also incl.	411.0	412.0	1.0	13.75	0.43	1.00	56
	Including	434.0	437.0	3.0	6.82	0.43	1.41	73
	also incl.	435.0	436.0	1.0	9.11	1.57	2.27	74:
21MYCD0220 ¹	Minyari	443.0	443.6	0.6	0.40	0.06	0.16	148
21MYCD0222 ¹	Minyari	12.0	26.0	14.0	0.16	0.19	0.16	47
21MYCD0222 ¹	Minyari	29.0	30.0	1.0	0.62	0.14	0.15	48
21MYCD0222 ¹	Minyari	38.0	39.0	1.0	1.86	0.02	0.08	3.
21MYCD0222 ¹	Minyari	48.0	49.0	1.0	0.11	0.13	1.93	21
21MYCD0222	Minyari	49.0	75.0	26.0	1.10	0.13	0.61	44
LIVI I CDUZZZ	Including	50.0	53.0	3.0	5.38	0.17	0.61	46
	also incl.	51.0	52.0	1.0	10.50	0.29	0.47	43
	Including	57.0	58.0	1.0	1.93	0.57	0.80	489
	Including	73.0	74.0		2.98	0.57	0.80	
21MYCD0222 ¹	Minyari	73.0 81.0	74.0 82.0	1.0 1.0	0.70	0.25	0.83	1,60 8
21MYCD0222 21MYCD0222 ¹	Minyari	87.0	90.0	3.0	0.70	0.04	0.05	1,73
21MYCD0222 ¹	Minyari	105.0	106.0	1.0	0.92	0.03	0.09	1,73
21MYCD0222 ¹	Minyari	130.0	131.0	1.0	0.44	0.03	0.06	3(
Z T 1 V 1 I C D U Z Z Z	iviiiiyatt	130.0	131.0	1.0	0.00	0.12	0.25	31

Notes: Table 1 intersections are length-weighted assay intervals reported using the following criteria: Intersection Interval = Nominal cut-off grade scenarios:

- 1.0m ≥ 0.40 ppm (g/t) gold;
- No top-cutting has been applied to these individual assay intervals; and
- Intersections are down hole lengths, true widths not known with certainty, refer to JORC Table 1 Section 2.

Table 2: Minyari Dome Project - 2021 Drill Hole Collar Locations (MGA Zone 51/GDA 20)

Hole ID	Deposit	Hole Type	Northing (m)	Easting (m)	RL (m)	Hole Depth (m)	Azimuth (°)	Dip (°)	Assay Stat
21MYC0198	Minyari	RC	7635458	423001	278	204	60	-58	Received
21MYC0199	Minyari	RC	7635428	422964	278	336	60	-58	Received
21MYC0201	Minyari	RC	7635374	422883	278	300	60	-58	Receive
21MYC0202	Minyari	RC	7635489	423060	280	102	60	-58	Receive
21MYC0204	Minyari	RC	7635373	422963	278	282	60	-58	Receive
21MYC0206	Minyari	RC	7635366	423047	278	150	60	-58	Receive
21MYC0208	Minyari	RC	7635308	422942	278	354	60	-58	Receive
21MYC0209	Minyari	RC	7635277	422910	279	216	60	-58	Receive
21MYC0210	Minyari	RC	7635329	423082	279	120	60	-58	Receive
21MYC0211	Minyari	RC	7635263	423074	278	270	60	-58	Partially R
21MYC0212	Minyari	RC	7635463	423072	278	150	60	-58	Receive
21MYC0213	Minyari	RC	7635446	422944	278	432	58	-54	Receive
21MYC0215	Minyari	RC	7635249	422863	278	416	58	-60	Receive
21MYC0217	Minyari	RC	7635299	423033	279	204	58	-60	Partially R
21MYC0218	Minyari	RC	7635272	422996	278	366	58	-60	Receive
21MYC0219	Minyari	RC	7635243	422955	279	402	58	-60	Partially F
21MYC0221	Minyari	RC	7635310	422934	278	432	58	-60	Receive
21MYC0223	Minyari	RC	7635316	423027	280	180	58	-60	Pendin
21MYC0224	Minyari	RC	7635245	422914	278	432	58	-59	Receive
21MYC0225	Minyari	RC	7635365	423098	278	132	58	-60	Receive
21MYC0226	Minyari	RC	7635225	422974	279	432	58	-60	Receive
21MYC0227	Minyari	RC	7635240	423035	279	360	58	-55	Partially F
21MYC0228	Minyari	RC	7635212	422989	279	300	58	-55	Receive
21MYC0229	Minyari	RC	7635185	422949	279	390	58	-55	Pendin
21MYC0230	Minyari	RC	7635397	423054	270	432	58	-60	Pendin
21MYC0230A	, Minyari	RC	7635395	423069	277	48	58	-60	Pendin
21MYC0231	Minyari	RC	7635445	422892	277	456	58	-60	Pendin
21MYC0232	Minyari	RC	7635391	422807	277	456	58	-60	Pendin
21MYC0233	Minyari	RC	7635355	422788	276	450	58	-55	Receive
21MYC0234	Minyari	RC	7635418	422850	276	456	58	-60	Pendin
21MYC0235	Minyari	RC	7635471	422935	277	402	58	-60	Partially F
21MYC0236	Minyari	RC	7635192	423008	278	350	58	-55	Receive
21MYC0237	Minyari	RC	7635005	422798	277	420	58	-55	Pendin
21MYC0238	Minyari	RC	7635115	422979	278	420	58	-55	Pendin
21MYC0239	WACA	RC	7634160	423040	280	462	58	-55	Pendin
21MYC0240	WACA	RC	7634574	422670	281	429	58	-55	Pendin
21MYC0240	WACA	RC	7634531	422700	281	432	58	-55	Pendin
21MYC0242	WACA	RC	7634533	422800	282	360	58	-58	Pendin
21MYC0242	WACA	RC	7634674	422645	279	444	58	-58	Pendin
21MYC0244	WACA	RC	7634598	422714	281	318	58	-55	Pendin
21MYC0244	WACA	RC	7634472	423457	281	456	238	-53 58	Pendin
21MYC0245	WACA	RC	7634472	423437	281	360	58	-55	Pendin
21MYC0246 21MYC0247	WACA	RC	7634670	423113	279	450	58	-55 -58	Pendin
21MYC0247 21MYC0248	WACA	RC	7634663	422546	279	438	58	-58 -55	Pendin
21MYC0249	WACA	RC	7634497	422836	279	300	58	-58	Pendin


Hole ID	Deposit	Hole Type	Northing (m)	Easting (m)	RL (m)	Hole Depth (m)	Azimuth (°)	Dip (°)	Assay State
21MYC0251	WACA	RC	7634625	422757	279	138	58	-55	Pending
21MYC0252	WACA	RC	7634462	422874	279	240	58	-55	Pending
21MYC0253	WACA	RC	7634388	422944	279	150	58	-55	Pending
21MYC0254	WACA	RC	7634351	422984	282	258	58	-55	Pending
21MYC0255	Minyari	RC	7635131	423003	290	102	58	-58	Pending
21MYC0256	Minyari	RC	7635046	422853	297	450	58	-58	Pending
21MYC0257	Minyari	RC	7635204	422073	283	450	58	-58	Pending
21MYC0258	Minyari	RC	7635180	423083	272	354	58	-58	Pending
21MYC0259	Minyari	RC	7635232	423066	258	276	58	-58	Pending
21MYC0261	Minyari	RC	7635030	422938	282	282	58	-58	Pending
21MYC0262	Minyari	RC	7635139	423174	268	378	58	-58	Pending
21MYC0263	Minyari	RC	7635071	423096	283	180	58	-58	Pending
21MYC0264	Minyari	RC	7635158	4229989	276	252	58	-58	Pending
21MYC0265	Minyari	RC	7634939	422937	279	144	58	-58	Pending
21MYC0266	Minyari	RC	7634960	422960	245	102	58	-58	Pending
21MYC0267	Minyari	RC	7634906	422917	288	126	58	-58	Pending
21MYC0268	Minyari	RC	7634939	422965	274	72	58	-58	Pending
21MYC0269	Minyari	RC	7635046	423173	281	114	58	-58	Pending
21MYC0270	Minyari	RC	7635106	423249	285	120	58	-58	Pending
21MYC0271	Minyari	RC	7635501	422980	276	282	58	-55	Pending
21MYC0272	Minyari	RC	7635443	423046	277	300	58	-55	Pending
21MYC0273	Minyari	RC	7635340	422948	302	450	58	-55	Pending
21MYC0275	Minyari	RC	7635162	422835	322	468	57	-55	Pending
21MYC0276	, Minyari	RC	7635305	422990	273	138	58	-58	Pending
21MYC0277	, Minyari	RC	7635206	422883	283	288	58	-55	Pending
21MYC0278	Minyari	RC	7635232	422504	280	216	58	-55	Pending
21MYC0279	Minyari	RC	7635435	422736	323	318	58	-55	Pending
21MYC0280	Minyari	RC	7635312	422962	283	468	58	-58	Pending
21MYC0281	WACA	RC	7635244	422761	276	150	58	-58	Pending
21MYC0282	WACA	RC	7634510	422721	288	204	58	-55	Pending
21MYC0283	WACA	RC	7634486	422771	300	222	58	-55	Pending
21MYC0284	WACA	RC	7634512	422813	297	156	58	-55	Pending
21MYC0287	WACA	RC	7634413	422748	294	198	58	-55	Pending
21MYC0287	WACA	RC	7634439	422798	318	180	58	-55	Pending
21MYC0288	WACA	RC	7634467	422738	284	180	58	-55	Pending
21MYC0289 21MYC0291	WACA	RC	7634407	422832	278	180	58	-55 -55	Pending
21MYC0291 21MYC0292	WACA	RC	7634439	422832	278	102	58	-55 -55	Pending
21MYC0292 21MYC0295	WACA	RC	7634397	422913	265	60	58	-55 -55	Pending
21MYC0295 21MYC0296			7634397	422913	268				Pending
21MYD0500A	WACA	RC DD	7635243	422900	208	80 819	238 57	-55 -57	Partially R
	Minyari								
21MYD0501	Minyari	DD	7635235	422790	276	658	57	-55 E6	Pending
21MYD0502	Minyari	DD	7635227	422587	276	1027	56	-56 60	Pending
21MYD0503	Minyari	DD	7635280	422580	276	955	56	-60	Pending
21MYD0505	WACA	DD	7634555	422545	279	636	58	-52 52	Pending
21MYD0506	WACA	DD	7634445	422610	280	602	58	-52	Pending
21MYD0507	Minyari	DD	7635288	422832	277	559	55	-63	Pending
21MYD0508	Minyari	DD	7635452	422668	275	661	58	-62	Pending
21MYD0509	Minyari	DD	7635326	422653	274	800	57	-62	Pending

Hole ID	Deposit	Hole Type	Northing (m)	Easting (m)	RL (m)	Hole Depth (m)	Azimuth (°)	Dip (°)	Assay Status
21MYD0510	Minyari	DD	7635379	422741	277	616	58	-62	Pending
21MYD0511	WACA	DD	7634332	422663	279	560	59	-58	Pending
21MYD0512	Minyari	DD	7635257	422777	279	700	58	-58	Pending
21MYCD0200	Minyari	DD TAIL	7635405	422924	276	548	54	-58	Pending
21MYCD0203	Minyari	DD TAIL	7635403	423004	279	463	64	-58	Pending
21MYCD0205	Minyari	DD TAIL	7635353	422928	279	613	60	-58	Pending
21MYCD0207	Minyari	DD TAIL	7635337	422998	278	495	57	-57	Pending
21MYCD0214	Minyari	DD TAIL	7635401	422864	276	705	63	-56	Pending
21MYCD0216	Minyari	DD TAIL	7635344	422782	278	618	58	-55	Received
21MYCD0220	Minyari	DD TAIL	7635370	422908	277	548	58	-60	Partially Rec.
21MYCD0222	Minyari	DD TAIL	7635434	423013	277	448	58	-60	Partially Rec.
21MYRCBH2	Water	RC	7635105	422523	261	72	-	-90	Received
21MYRCBH3	Bores	RC	7635279	422914	264	66	-	-90	Received

Notes: Drill Hole Collar Table:

[•] Refer to JORC Table 1 Section 1 for full drill hole information; including drill technique, sampling, and analytical details.

About Antipa Minerals: Antipa is a mineral exploration company focused on the Paterson Province in north-west Western Australia, home to Newcrest Mining's world-class Telfer gold-copper mine, Rio Tinto's Winu copper-gold deposit, Greatland Gold-Newcrest's recent Havieron gold-copper discovery and other significant mineral deposits. Having first entered the Paterson in 2011 when it was a less sought-after exploration address, the Company has used its early mover advantage to build an enviable tenement holding of ~5,200km², including the ~1,300km² Citadel Joint Venture Project with Rio Tinto (who currently holds a 65% joint venture interest), the ~2,200km2 Wilki Project that is subject to a \$60 million Farm-in and Joint Venture Agreement with Newcrest (who is yet to earn a joint venture interest) and the ~1,500km² Paterson Project that is subject to a \$30 million Farm-in and Joint Venture Agreement with IGO (who is yet to earn a joint venture interest). The Citadel Project lies within 5km of the Winu deposit and contains a Mineral Resource of 2.4 million ounces of gold and 162,000 tonnes of copper from two deposits, Calibre and Magnum. Antipa retains 144km² of 100%-owned Minyari Dome Project tenements which contains an established Mineral Resource, with the Minyari and WACA deposits containing 723,000 ounces of gold and 26,000 tonnes of copper plus other deposits and high quality exploration targets. Unlike certain parts of the Paterson where the post mineralisation (younger) cover can be kilometres thick, making for difficult exploration, the Company's combined 5,200km² tenement portfolio features relatively shallow cover; approximately 80% being under less than 80 metres of cover. Extensive drilling and geophysical surveys are planned for 2021 across Antipa's combined Paterson tenement portfolio as the company pursues a dual strategy of targeting tier-one greenfields discoveries and growing its existing resources through brownfields exploration.



Forward-Looking Statements: This document may include forward-looking statements. Forward-looking statements include, but are not limited to, statements concerning Antipa Mineral Ltd's planned exploration programme and other statements that are not historical facts. When used in this document, the words such as "could," "plan," "estimate," "expect," "intend," "may," "potential," "should," and similar expressions are forward-looking statements. Although Antipa Minerals Ltd believes that its expectations reflected in these forward-looking statements are reasonable, such statements involve risks and uncertainties and no assurance can be given that actual results will be consistent with these forward-looking statements.

3 December 2015

Competent Persons Statement – Exploration Results: The information in this document that relates to Exploration Results is based on and fairly represents information and supporting documentation compiled by Mr Roger Mason, a Competent Person who is a Member of The Australasian Institute of Mining and Metallurgy. Mr Mason is a full-time employee of the Company. Mr Mason is the Managing Director of Antipa Minerals Limited, is a substantial shareholder of the Company and is an option holder of the Company. Mr Mason has sufficient experience relevant to the style of mineralisation and type of deposit under consideration and to the activity being undertaking to qualify as a Competent Person as defined in the 2012 Edition of the 'Australasian Code for Reporting of Exploration Results, Mineral Resources and Ore Reserves'. The Company confirms that the form and context in which the Competent Person's findings are presented have not been materially modified from the original market announcements, all of which are available to view on www.asx.com.au. Mr Mason, whose details are set out above, was the Competent Person in respect of the Exploration Results in these original market announcements.

Various information in this report which relates to Exploration Results have been extracted from the following announcements lodged on the ASX, where further details, including JORC Code reporting tables where applicable, can also be found:

North Telfer Project Update on Former NCIVI Mining Leases	3 December 2015
High Grade Gold Mineralisation at Minyari Dome	8 February 2016
Minyari Deposit Drilling to Commence May 2016	2 May 2016
Minyari Phase 1 Drilling Commences	2 June 2016
Further Historical High-grade Gold Intersections at Minyari	14 June 2016
Minyari Reprocessed IP Survey Results	5 July 2016
Minyari Phase 1 Drilling Update No. 1	20 July 2016
Completion of Phase 1 Minyari Deposit RC Drilling Programme	9 August 2016
Minyari Drilling Update No. 3	17 August 2016
Minyari Drilling Update No. 4	29 September 2016
Minyari Dome - Phase 2 Exploration Programme Commences	31 October 2016
North Telfer and Citadel Exploration Programme Update	16 November 2016
Minyari Dome Drilling Update No. 1	16 December 2016
Minyari Dome and Citadel – Phase 2 Update	9 February 2017
Minyari Dome 2017 Exploration Programme	27 March 2017
Minyari Dome 2017 Phase 1 Exploration Programme Commences	13 April 2017
Minyari Dome Positive Metallurgical Test Work Results	13 June 2017
High-Grade Gold Intersected at North Telfer Project Revised	21 June 2017
Drilling Extends High-Grade Gold Mineralisation at WACA	25 July 2017
High-Grade Gold Mineralisation Strike Extension at Minyari Deposit	4 August 2017
Minyari Dome Phase 1 Final Assay Results	31 August 2017
Minyari/WACA Deposits Maiden Mineral Resource	16 November 2017
Air Core Programme Highlights Minyari and WACA Deposit	5 December 2017
Minyari Dome 2017 Air Core Drilling Results	29 January 2018
Antipa to Commence Major Exploration Programme	1 June 2018
Major Exploration Programme Commences	25 June 2018
2018 Exploration Programme Update	16 July 2018
Minyari Dome – Initial Drill Results	1 August 2018
Thick High-grade Copper Mineralisation Intersected	2 October 2018
Chicken Ranch and Minyari Dome Drilling Update	15 November 2018
Multiple New Gold-Copper Targets on 100% Owned Ground	23 December 2019
Commencement of Drilling Programmes at Minyari Dome Project	2 October 2020
Drilling of New Targets Deliver Significant Au Intersections	16 February 2021
High-Grade Gold Intersected at Minyari & WACA Deposits	7 April 2021
Commencement of Drilling at 100% Owned Minyari Project	13 May 2021
AZY: 2021 Exploration Activities Update	17 June 2021
Discovery of Significant Zones of High-Grade Gold at Minyari	15 July 2021
Further High-Grade Gold Mineralisation at Minyari Deposit	20 July 2021
Further High-Grade Gold Results at 100% Minyari Deposit	12 August 2021
Outstanding Gold Intersections at 100% Owned Minyari Deposit	6 September 2021

North Telfer Project Update on Former NCM Mining Leases

These announcements are available for viewing on the Company's website www.antipaminerals.com.au under the Investors tab and on the ASX website www.asx.com.au.

The Company confirms that the form and context in which the Competent Person's findings are presented have not been materially modified from the original market announcements. Mr Roger Mason, whose details are set out above, was the Competent Person in respect of the Exploration Results in these original reports.

Competent Persons Statement – Mineral Resource Estimations for the Minyari-WACA Deposits, Calibre Deposit, Tim's Dome and Chicken Ranch Deposits, and Magnum Deposit: The information in this document that relates to the estimation and reporting of the Minyari-WACA deposits Mineral Resources is extracted from the report entitled "Minyari/WACA Deposits Maiden Mineral Resources" created on 16 November 2017 with Competent Persons Kahan Cervoj and Susan Havlin, the Calibre deposit Mineral Resource is extracted from the report entitled "Calibre Gold Resource Increases 62% to 2.1 Million Ounces" created on 17 May 2021 with Competent Person lan Glacken, the Tim's Dome and Chicken Ranch deposits Mineral Resources is extracted from the report entitled "Chicken Ranch and Tims Dome Maiden Mineral Resources" created on 13 May 2019 with Competent Person Shaun Searle, and the Magnum deposit Mineral Resource information is extracted from the report entitled "Calibre and Magnum Deposit Mineral Resource JORC 2012 Updates" created on 23 February 2015 with Competent Person Patrick Adams, all of which are available to view on www.antipaminerals.com.au and www.asx.com.au. The Company confirms that it is not aware of any new information or data that materially affects the information included in the original market announcements and that all material assumptions and technical parameters underpinning the estimates in the relevant original market announcements continue to apply and have not materially changed. The Company confirms that the form and context in which the Competent Person's findings are presented have not been materially modified from the original market announcements.

Gold Metal Equivalent Information - Calibre Mineral Resource Gold Equivalent cut-off grade: Gold Equivalent (Aueq) details of material factors and metal equivalent formula are reported in "Calibre Gold Resource Increases 62% to 2.1 Million Ounces" created on 17 May 2021 which is available to view on www.asx.com.au and www.asx.com.au.

Gold Metal Equivalent Information - Magnum Mineral Resource Gold Equivalent cut-off grade: Gold Equivalent (Aueq) details of material factors and metal equivalent formula are reported in "Citadel Project - Calibre and Magnum Deposit Mineral Resource JORC 2012 Updates" created on 23 February 2015 which is available to view on www.antipaminerals.com.au and www.asx.com.au.

Mineral Resource Estimates

Minyari Dome Project (100% Antipa)

Deposit and Gold Cut-off Grade*	Resource Category	Tonnes (Mt)	Gold Grade (g/t)	Copper Grade (%)	Silver Grade (g/t)	Cobalt (ppm)	Gold (oz)	Copper (t)	Silver (oz)	Cobalt (t)
Minyari 0.5 Au	Indicated	3.2	1.9	0.3	0.7	590	192,610	9,600	75,660	1,860
Minyari 0.5 Au	Inferred	0.7	1.7	0.24	0.6	340	36,260	1,560	13,510	220
Minyari 0.5 Au	Sub-Total	3.8	1.9	0.29	0.7	550	228,870	11,160	89,170	2,080
Minyari 1.7 Au	Indicated	.2	2.6	0.29	0.9	430	18,740	650	6,800	100
Minyari 1.7 Au	Inferred	3.7	2.6	0.3	1.0	370	303,000	10,950	117,550	1,360
Minyari 1.7 Au	Sub-Total	3.9	2.6	0.3	1.0	380	321,740	11,600	124,350	1,460
Minyari	Total	7.7	2.2	0.3	0.9	460	550,610	22,760	213,520	3,540
WACA 0.5 Au	Inferred	2.8	1.4	0.11	0.2	180	121,950	3,120	15,920	500
WACA 1.7 Au	Inferred	0.5	2.9	0.09	0.2	230	50,780	510	3,850	120
WACA	Total	3.3	1.6	0.11	0.2	190	172,730	3,630	19,770	620
Minyari + WACA Deposits	Grand Total	11.0	2.0	0.24	0.7	380	723,340	26,390	233,290	4,160

^{*0.5} Au = Using a 0.5 gft gold cut-off grade above the 50mRL (NB: potential "Open Cut" cut-off grade) and *1.7 Au = Using a 1.7 gft gold cut-off grade below the 50mRL (NB: potential "Underground" cut-off grade)

Wilki Project (Newcrest Farm-in)

Deposit and Gold Cut-off Grade**	Resource Category	Tonnes (Mt)	Gold Grade (g/t)	Copper Grade (%)	Silver Grade (g/t)	Cobalt (ppm)	Gold (oz)	Copper (t)	Silver (oz)	Cobalt (t)
Chicken Ranch Area 0.5 Au	Inferred	0.8	1.6	17		-	40,300	1573		
Tim's Dome 0.5 Au	Inferred	1.8	1.1	-	2	2:	63,200	121	-	æ
Chicken Ranch Area + Tim's Dome	Total	2.4	1.3	15	8	ē	103,500	(2)	170	æ

^{**0.5} Au = Using a 0.5 g/t gold cut-off grade above the 50mRL (NB: potential "Open Cut" cut-off grade)

Citadel Project (Rio Tinto JV)

Deposit and Gold Cut-off Grade***	Resource Category	Tonnes (Mt)	Gold Equiv (g/t)	Gold Grade (g/t)	Copper Grade (%)	Silver Grade (g/t)	Gold Equiv (Moz)	Gold (Moz)	Copper (t)	Silver (Moz)
Calibre 0.5 Au Equiv	Inferred	92	0.92	0.72	0.11	0.46	2.7	2.1	104,000	1.3
Magnum 0.5 Au Equiv	Inferred	16	-	0.70	0.37	1.00	3 4 3	0.34	58,000	0.5
Calibre + Magnum Deposits	Total	108	s	0.72	0.15	0.54	2.7	2.4	162,000	1.8

^{***0.5} AuEquiv = Refer to details provided by the Notes section

Note: Citadel Project Mineral Resources are tabled on a 100% basis, with Antipa's current joint venture interest being 35%

Note: Wilki Project Mineral Resources are tabled on a 100% basis, with Antipa's current joint venture interest being 100%

MINYARI DOME PROJECT – 2021 Minyari and WACA Reverse Circulation & Diamond Drill Hole Sampling Section 1 – Sampling Techniques and Data (Criteria in this section shall apply to all succeeding sections)

Criteria	JORC Code explanation	Commentary
Sampling techniques	 Nature and quality of sampling (e.g. cut channels, random chips, or specific specialised industry standard measurement tools appropriate to the minerals under investigation, such as down hole gamma sondes, or handheld XRF instruments, etc). These examples should not be taken as limiting the broad meaning of sampling. Include reference to measures taken to ensure sample representivity and the appropriate calibration of any measurement tools or systems used. Aspects of the determination of mineralisation that are Material to the Public Report. In cases where 'industry standard' work has been done this would be relatively simple (e.g. 'reverse circulation drilling was used to obtain 1 m samples from which 3 kg was pulverised to produce a 30 g charge for fire assay'). In other cases more explanation may be required, such as where there is coarse gold that has inherent sampling problems. Unusual commodities or mineralisation types (e.g. submarine nodules) may warrant disclosure of detailed information. 	 The Minyari & WACA deposits have been sampled by 87 Reverse Circulation (RC) drill holes, totaling 24,643m with an average maximum drill hole depth of 283m. Assay results have been received for 22 RC drill holes, with partial results received for 5 other drill holes. The nominal drill hole spacing is across multiple east-west local grid sections spaced 50m apart with an average drill hole spacing on each section of 50m. To date in 2021 at the Minyari deposit, three 25m infill sections have been completed with average drill spacing of 50m on section. Drill hole locations for all RC holes are tabulated in the body of this report. RC Sampling RC Sampling was carried out under Antipa protocols and QAQC procedures as per industry best practice. RC samples were drilled using a 140mm diameter face sampling hammer and sampled on intervals of 1.0m. In known zones of mineralisation, two 1m samples were collected as a split from the rig mounted cone splitter and are on average 3kg in weight. The samples were pulverised at the laboratory to produce material for assay. Composite samples of 3-4m intervals were taken in known unmineralised regions. Samples were taken either directly from the rig mounted core splitter, or via combining "Spear" samples of the unmineralised sample intervals to generate a 2-3 kg sample. Each sample was pulverised at the laboratory to produce material for assay.
		 2021 Diamond Drilling (DD) The Minyari & WACA deposits have been drilled by 12 diamond drill (DD) holes totalling 8,593m with an average maximum hole depth of 716m. Designed DD hole lengths range from 560m to 1027m. Additionally, 8 diamond tails have been drilled totalling 1516m. Assay results have been received for 1 diamond drill hole and 1 diamond tail. Partial results have been received for 2 additional diamond tails. Diamond drill holes were drilled on a range of hole spacings along line and across line. Drill hole locations and orientations for all 2021 holes are tabulated in the body of this report Diamond Core Sampling Diamond core sampling was carried out under Antipa protocols and QAQC procedures as per

Criteria	JORC Code explanation	Commentary
Dillin		 industry best practice. All diamond drill core samples were cut in half with an automatic core saw. All available half core was sampled, nominally as one metre samples but at times adjusted for major geological changes. Samples range between 0.3m and 1.2m. Half diamond drill core samples are prepared for assay and the remaining half core archived. All drill core was logged and photographed by the geology team prior to cutting.
Drilling techniques	Drill type (e.g. core, reverse circulation, open-hole hammer, rotary air blast, auger, Bangka, sonic, etc) and details (e.g. core diameter, triple or standard tube, depth of diamond tails, face-sampling bit or other type, whether core is oriented and if so, by what method, etc).	 Reverse Circulation (RC) Drilling All drill holes were completed using 140mm RC face sampling hammer drill bit from surface to total drill hole depths of between 100m to 450m. Diamond Core Holes Diamond drill holes were completed using PQ at the start of hole to a designated depth depending on ground conditions, followed by HQ to a designated depth, then NQ to the end of hole. Diamond tail depths ranged from 460m to 706m, with an average tail length of 195m. All core was orientated using a Reflex ACT electronic orientation tool.
Drill sample recovery	 Method of recording and assessing core and chip sample recoveries and results assessed. Measures taken to maximise sample recovery and ensure representative nature of the samples. Whether a relationship exists between sample recovery and grade and whether sample bias may have occurred due to preferential loss/gain of fine/coarse material. 	 Reverse Circulation (RC) Drill Samples RC sample recovery was recorded via visual estimation of sample volume, typically ranging from 90 to 100%, with only very occasional samples with less than 70% recovery. RC sample recovery was maximized by endeavoring to maintain a dry drilling conditions as much as practicable; the majority of RC samples were dry. All samples were split using a rig-mounted cone splitter. Adjustments were made to ensure representative 2 to 3kg sample volumes were collected. Relationships between recovery and grade are not evident and are not expected given the generally excellent and consistently high sample recovery. Diamond Core Holes Core recovery is recorded as a percentage. Overall core recoveries averaged over 99.5% and there are no core loss issues or significant sample recovery problems except for occasional very localised/limited regions Drillers used appropriate measures to maximise diamond sample recovery. There is no relationship between sample recovery and/or grade warranted as the mineralisation is defined by diamond core drilling which has high recoveries.
Logging	 Whether core and chip samples have been geologically and geotechnically logged to a level of detail to support appropriate Mineral Resource estimation, mining studies and metallurgical studies. Whether logging is qualitative or quantitative in nature. Core (or costean, channel, etc) photography. The total length and percentage of the relevant intersections 	 Geological logging of all RC and DD sample intervals was carried out recording colour, weathering, lithology, mineralogy, alteration, veining and sulphides. Logging includes both qualitative and quantitative components. Logging was completed for 100% of all holes drilled. All logging is entered directly into a notebook computer using the Antipa Proprietary Logging System which is based on Microsoft Excel. The logging system uses standard look up tables that does not

Criteria	JORC Code explanation	Commentary
	logged.	 allow invalid logging codes to be entered. Further data validation is carried out during upload to Antipa's master Access SQL database. All RC sample intervals were measured for magnetic susceptibility using a handheld Magnetic Susceptibility meter. Geotechnical logging of all DD core was carried out for Recovery, RQD and Fracture Frequency. Information on structure type, dip, dip direction, alpha angle, beta angle, gamma angle, texture and fill material is stored in the Company's technical database.
Sub-sampling techniques and sample preparation	 If core, whether cut or sawn and whether quarter, half or all core taken. If non-core, whether riffled, tube sampled, rotary split, etc and whether sampled wet or dry. For all sample types, the nature, quality and appropriateness of the sample preparation technique. Quality control procedures adopted for all sub-sampling stages to maximise representivity of samples. Measures taken to ensure that the sampling is representative of the in situ material collected, including for instance results for field duplicate/second-half sampling. Whether sample sizes are appropriate to the grain size of the material being sampled. 	 RC sampling RC samples for all drill holes were drilled using a 140mm diameter face sampling hammer and split on intervals of 1.0m using a rig mounted cone splitter from which two 3 kg (average) samples were collected. The majority of the samples were dry. Composite samples of 3-4m intervals were taken in known unmineralised regions. Samples were taken either directly from the rig mounted core splitter, or via combining "Spear" samples of the unmineralised sample intervals to generate a 2-3 kg sample. Each sample was pulverised at the laboratory to produce material for assay. Sample preparation was carried out at ALS using industry standard crush and/or pulverizing techniques. Preparation includes over drying and pulverizing of the entire sample using Essa LM5 grinding mill to a grid size of 85% passing 75 μm. Field duplicate samples were collected for all RC drill holes. The sample sizes are considered appropriate for the style of mineralisation at the Minyari and WACA deposits. Diamond Drill Core Sampling Diamond core is sampled as half core on a nominal 1.0m sample interval within unmineralised zones and on 0.3 to 1.2m intervals within the mineralised zones. Sample preparation was carried out at ALS using industry standard crush and/or pulverizing techniques. Preparation includes over drying and pulverizing of the entire sample using Essa LM5 grinding mill to a grid size of 85% passing 75 μm. The sample sizes are considered appropriate for the style of mineralisation at the Minyari and WACA deposits.
Quality of assay data and laboratory tests	 The nature, quality and appropriateness of the assaying and laboratory procedures used and whether the technique is considered partial or total. For geophysical tools, spectrometers, handheld XRF instruments, etc, the parameters used in determining the analysis including instrument make and model, reading times, calibrations factors applied and their derivation, etc. Nature of quality control procedures adopted (e.g. standards, 	 All samples were submitted to ALS in Perth for preparation and analysis. All samples were dried, crushed, pulverised and split to produce a sub–sample of 25g which is digested and refluxed with hydrofluoric, nitric, hydrochloric and perchloric acids ("four acid digest"). This digest is considered to approach a total dissolution for most minerals. Analytical analysis is performed using a combination of ICP-AES and ICP-MS. (Ag, Al, As, Ba, Be, Bi, Ca, Cd, Ce, Co, Cr, Cu, Fe, K, La, Li, Mg, Mn, Mo, Na, Ni, P, Pb, S, Sb, Sc, Sn, Sr, Te, Ti, Tl, V, W and Zn). A lead collection fire assay on a 50g sample with Atomic Absorption Spectroscopy undertaken to

Criteria	JORC Code explanation	Commentary
	blanks, duplicates, external laboratory checks) and whether acceptable levels of accuracy (i.e. lack of bias) and precision have been established.	 determine gold content with a detection limit of 0.005ppm. Additional ore-grade analysis was performed as required for other elements reporting out of range. Field QC procedures involve the use of commercial certified reference material (CRM's) for assay standards and blanks. Standards are inserted every 25 samples. The grade of the inserted standard is not revealed to the laboratory. Field duplicates/repeat QC samples was utilised during the RC drilling programme with nominally 1 in 30 duplicate samples submitted for assaying for each drill hole. Inter laboratory cross-checks analysis programmes have not been conducted at this stage. In addition to Antipa supplied CRM's, ALS includes in each sample batch assayed certified reference materials, blanks and up to 10% replicates. If necessary, selected anomalous samples are re-digested and analysed to confirm results.
Verification of sampling and assaying	 The verification of significant intersections by either independent or alternative company personnel. The use of twinned holes. Documentation of primary data, data entry procedures, data verification, data storage (physical and electronic) protocols. Discuss any adjustment to assay data. 	 Significant intersections of the drilling have been visually verified by the Exploration Manager. There have been no twinned RC holes at this current stage of the drill programme. All logging is entered directly into a notebook computer using the Antipa Proprietary Logging System which is based on Microsoft Excel. The logging system uses standard look up tables that does not allow invalid logging codes to be entered. Further data validation is carried out during upload to Antipa's master SQL database. No adjustments or calibrations have been made to any assay data collected.
Location of data points	 Accuracy and quality of surveys used to locate drill holes (collar and down-hole surveys), trenches, mine workings and other locations used in Mineral Resource estimation. Specification of the grid system used. Quality and adequacy of topographic control. 	 km = kilometre; m = metre; mm = millimetre. Drill hole collar locations are surveyed using a handheld Garmin 64S GPS which has an accuracy of ± 3m. The drilling co-ordinates are all in GDA20 MGA Zone 51 co-ordinates. The Company has adopted and referenced one specific local grid across the Minyari Dome region ("Minyari" Local Grid) which is defined below. References in the text and the Minyari deposit diagrams are all in this specific Minyari Local Grid. Minyari Local Grid 2-Point Transformation Data: Minyari Local Grid 47,400m east is 421,462.154m east in GDA94 / MGA Zone 51; Minyari Local Grid 99,000m north is 7,632,467.588 m north in GDA94 / MGA Zone 51; Minyari Local Grid 47,400m east is 414,078.609m east in GDA94 / MGA Zone 51; Minyari Local Grid 113,000m north is 7,644,356.108m north in GDA94 / MGA Zone 51; Minyari Local Grid North (360°) is equal to 330° in GDA94 / MGA Zone 51; Minyari Local Grid elevation is equal to GDA20 / MGA Zone 51. The topographic surface has been defaulted to 277m RL. For RC holes, rig orientation was checked using Suunto Sighting Compass from two directions. Drill hole inclination was set by the driller using a clinometer on the drill mast and checked by the geologist prior the drilling commencing.

Criteria	JORC Code explanation	Commentary
		 Diamond drill holes are aligned using an azimuth aligner tool. The topographic surface has been compiled using the drill hole collar coordinates. Surveys were completed upon hole completion using a Reflex Gyro downhole survey instrument. Down hole single shots were completed on all diamond holes for hole tracking. Surveys were checked by the supervising geologist for consistency. If required, readings were resurveyed or smoothed in the database if unreliable azimuth readings were apparent. Survey details included drill hole dip (±0.25° accuracy) and drill hole azimuth (±0.35 accuracy°), Total Magnetic field and temperature.
Data spacing and distribution	 Data spacing for reporting of Exploration Results. Whether the data spacing and distribution is sufficient to establish the degree of geological and grade continuity appropriate for the Mineral Resource and Ore Reserve estimation procedure(s) and classifications applied. Whether sample compositing has been applied. 	 RC drill hole spacing is east-west 'Minyari grid' sections spaced approximately 50m apart with an 50m average drill hole spacing on each section. To date in 2021 three 25m infill RC drill sections have been completed with average drill spacing of 50m at the Minyari deposit. Diamond core holes were drilled on a range of hole spacings along line and across line. The section spacing is sufficient to establish the degree of geological and grade continuity necessary to support Mineral Resource estimations. No sample compositing has been applied for the reporting of RC and DD results.
Orientation of data in relation to geological structure	 Whether the orientation of sampling achieves unbiased sampling of possible structures and the extent to which this is known, considering the deposit type. If the relationship between the drilling orientation and the orientation of key mineralised structures is considered to have introduced a sampling bias, this should be assessed and reported if material. 	 The location and orientation of the Minyari RC drilling is appropriate given the strike, dip and morphology of the mineralisation. Minyari deposit holes are angled towards local grid east to be perpendicular to the strike of both the dominant mineralisation trend, and at a suitable angle to the dip of the dominant mineralisation. No consistent and/or material sampling bias resulting from a structural orientation has been identified at Minyari at this stage; however, both folding and multiple vein directions have been recorded via surface mapping, diamond drilling and RC drilling.
Sample security	The measures taken to ensure sample security.	 Chain of sample custody is managed by Antipa to ensure appropriate levels of sample security. Samples are stored on site and delivered by Antipa or their representatives to Port Hedland and subsequently by Toll Transport from Port Hedland to the assay laboratory in Perth.
Audits or reviews	The results of any audits or reviews of sampling techniques and data.	 Sampling techniques and procedures are regularly reviewed internally, as is the data. Consultants Snowden, during completion of the 2013 Calibre Mineral Resource estimate, undertook a desktop review of the Company's sampling techniques and data management and found them to be consistent with industry standards.

MINYARI DOME PROJECT

Section 2 – Reporting of Exploration Results (Criteria listed in the preceding section also apply to this section)

Criteria	JORC Code explanation	Commentary
Mineral tenement and land tenure status	 Type, reference name/number, location and ownership including agreements or material issues with third parties such as joint ventures, partnerships, overriding royalties, native title interests, historical sites, wilderness or national park and environmental settings. The security of the tenure held at the time of reporting along with any known impediments to obtaining a licence to operate in the area. 	 The Minyari and WACA deposit drilling and other exploration data is located wholly within Exploration License E45/3919 (granted). Antipa Minerals Ltd has a 100% interest in E45/3919. A 1% net smelter royalty payable to Paladin Energy on the sale of product on all metals applies to this tenement as a condition of a Split Commodity Agreement with Paladin Energy. E45/3919 is not subject to the Citadel Project Farm-in Agreement with Rio Tinto Exploration Pty Ltd. The tenement is contained completely within land where the Martu People have been determined to hold native title rights. To the Company's knowledge no historical or environmentally sensitive sites have been identified in the area being actively explored. The tenement is in good standing and no known impediments exist.
Exploration done by other parties	Acknowledgment and appraisal of exploration by other parties.	 The Minyari and WACA deposits were greenfield discoveries by the Western Mining Corporation Ltd during the early 1980's. Exploration of the Minyari Dome region has involved the following companies: Exploration of the Minyari Dome region has involved the following companies: Western Mining Corporation Ltd (1980 to 1983); Newmont Holdings Pty Ltd (1984 to 1990); MIM Exploration Pty Ltd (1990 to 1991); Newcrest Mining Limited (1991 to 2015); and Antipa Minerals Ltd (2016 onwards).
Geology	Deposit type, geological setting and style of mineralisation.	The geological setting is Paterson Province Proterozoic aged meta-sediment hosted hydrothermal shear, fault and strata/contact controlled precious and/or base metal mineralisation which is typically sulphide bearing. The mineralisation in the region is interpreted to be granite related. The Paterson is a low grade metamorphic terrane but local hydrothermal alteration and/or contact metamorphic mineral assemblages and styles are indicative of a high-temperature local environment. Mineralisation styles include vein, stockwork, breccia and skarns.
Drill hole Information	 A summary of all information material to the understanding of the exploration results including a tabulation of the following information for all Material drill holes: easting and northing of the drill hole collar elevation or RL (Reduced Level – elevation above sea level in metres) of the drill hole collar dip and azimuth of the hole down hole length and interception depth hole length. 	 A summary of all available information material to the understanding of the Minyari Dome region exploration results can be found in previous WA DMIRS publicly available reports. All the various technical Minyari Dome region exploration reports are publicly accessible via the DMIRS' online WAMEX system. The specific WAMEX and other reports related to the exploration information the subject of this public disclosure have been referenced in previous public reports.

Criteria	JORC Code explanation	Commentary
	If the exclusion of this information is justified on the basis that the information is not Material and this exclusion does not detract from the understanding of the report, the Competent Person should clearly explain why this is the case.	
Data aggregation methods	 In reporting Exploration Results, weighting averaging techniques, maximum and/or minimum grade truncations (e.g. cutting of high grades) and cut-off grades are usually Material and should be stated. Where aggregate intercepts incorporate short lengths of high grade results and longer lengths of low grade results, the procedure used for such aggregation should be stated and some typical examples of such aggregations should be shown in detail. The assumptions used for any reporting of metal equivalent values should be clearly stated. 	 No weighted average techniques have been used to report results from RC drilling. Weighted average techniques have been applied to report results from DD drilling. No top-cuts to gold, copper, silver or cobalt have been applied (unless specified otherwise). A nominal 0.40 g/t gold, 0.10% copper, 0.75 g/t silver and 400ppm cobalt lower cut-off grades have been applied during data aggregation. Higher grade intervals of mineralisation internal to broader zones of mineralisation are reported as included intervals. Metal equivalence is not used in this report.
Relationship between mineralisation widths and intercept lengths	 These relationships are particularly important in the reporting of Exploration Results. If the geometry of the mineralisation with respect to the drill hole angle is known, its nature should be reported. If it is not known and only the down hole lengths are reported, there should be a clear statement to this effect (e.g. 'down hole length, true width not known'). 	Minyari Deposit (MGA grid)
Diagrams	Appropriate maps and sections (with scales) and tabulations of intercepts should be included for any significant discovery being reported These should include, but not be limited to a plan view of drill hole collar locations and appropriate sectional views.	All appropriate maps and sections (with scales) and tabulations of intercepts are reported or can sometimes be found in previous WA DMIRS WAMEX publicly available reports.
Balanced reporting	Where comprehensive reporting of all Exploration Results is not practicable, representative reporting of both low and high grades and/or widths should be practiced to avoid misleading reporting of Exploration Results.	All significant results are reported or can sometimes be found in previous WA DMIRS WAMEX publicly available reports.
Other substantive exploration data	Other exploration data, if meaningful and material, should be reported including (but not limited to): geological observations; geophysical survey results; geochemical survey results; bulk samples – size and method of treatment; metallurgical test results; bulk density, groundwater, geotechnical and rock characteristics; potential deleterious or contaminating substances.	 All meaningful and material information has been included in the body of the text or can sometimes be found in previous WA DMIRS WAMEX publicly available reports. The details of the Minyari Dome region historic Induced Polarisation survey, including IP Chargeability and resistivity anomalies, can be found in WA DMIRS publicly available WAMEX reports A81227 (2008), A86106 (2009) and A89687 (2010). The details of the Company's reprocessing, review and modelling of the Minyari Dome region historic Induced Polarisation survey, including IP Chargeability and resistivity anomalies, can be found in the Company's ASX report titled "Minyari Reprocessed IP Survey Results" created on 5 July 2016. Zones of mineralisation and associated waste material have not been measured for their bulk density; however, Specific Gravity ("Density") measurements continue to be taken from diamond

Criteria	JORC Code explanation	Commentary
		drill core. Multi element assaying was conducted variously for a suite of potentially deleterious elements including arsenic, sulfur, lead, zinc and magnesium. Downhole "logging" of a selection of Minyari deposit RC drillholes (i.e. 33 drill holes totalling 2,341m) was undertaken as part of the 2016 Phase 1 programme using an OBI40 Optical Televiewer which generated an oriented 360 degree image of the drill hole wall via a CCD camera recorded digital image. The OBI40 system utilised also included a North Seeking Gyro-scope to measure drill hole location/deviation, and the downhole survey also measured rock density, magnetic susceptibility, natural gamma and included a borehole caliper device for measuring drill hole diameter. The combined dataset collected via the OBI40 Optical Televiewer downhole survey data has multiple geological and geotechnical uses, including but not limited to the detection and determination of insitu lithological, structural and mineralisation feature orientations (i.e. dip and strike), determination and orientation of fracture frequency, general ground conditions/stability, oxidation conditions, ground-water table and clarity, etc. Information on structure type, dip, dip direction, alpha angle, beta angle, gamma angle, texture and fill material derived mainly from diamond drilling is stored in the Company's technical SQL database. No information on structure type, dip, dip direction, alpha angle, beta angle, gamma angle, texture and fill material were obtained from the WAMEX reports. Preliminary metallurgical test-work results are available for both the Minyari and WACA gold-coppersilver-cobalt deposits, these 13 June 2017 and 27 August 2018 metallurgical reports are available to view on www.antipaminerals.com.au (https://enipommerals.com.au/upload/documents/investor/sexanguncements/201129232007.2018-08-271.pdf) and www.asx.com.au. This preliminary metallurgical test-work was completed at the Bureau Veritas Minerals Pty Ltd laboratories in Perth, Western Australia under the manag

Criteria	JORC Code explanation	Commentary
		 appear the Newmont metallurgical test-work for these two bulk samples was never undertaken/competed as no results were subsequently reported to the WA DMIRS; Newmont Holdings Pty Ltd also collected drill hole metallurgical samples for Minyari deposit oxide and primary mineralisation (i.e. WAMEX 1986 report A19770); however, subsequent reporting of any results to the WA DMIRS could not be located suggesting that the metallurgical test-work was never undertaken/competed. Newcrest Mining Ltd describe the Minyari deposit gold-copper mineralisation as being typical of the Telfer gold-copper mineralisation. In 2004 and 2005 (WAMEX reports A71875 and A74417) Newcrest commenced metallurgical studies for the Telfer Mine and due to the similarities with the Minyari mineralisation a portion of this Telfer metallurgical test-work expenditure was apportioned to the then Newcrest Minyari tenements. Whilst Telfer metallurgical results are not publicly available, the Telfer Mining operation (including ore processing facility) was materially expanded in the mid-2000's and continues to operate with viable metallurgical recoveries (for both oxide and primary mineralisation).
Further work	 The nature and scale of planned further work (e.g. tests for lateral extensions or depth extensions or large-scale step-out drilling). Diagrams clearly highlighting the areas of possible extensions, including the main geological interpretations and future drilling areas, provided this information is not commercially sensitive. 	 Gold-copper-silver-cobalt mineralisation identified by the Company's 2021 drill programme the Minyari deposit has been intersected over a range of drill defined limits along strike, across strike and down dip and variously remains open in multiple directions with both deposits requiring further investigation/drilling to test for lateral and vertical mineralisation extensions and continuity beyond the limits of existing drilling limits. Project development studies, including further metallurgical test-work, geotechnical and mining evaluations. All appropriate maps and sections (with scales) and tabulations of intercepts are reported or can sometimes be found in previous WA DMIRS WAMEX publicly available reports.